


# BEGA

File: 12130K4\_BEGA\_IES.ies

TEST: BE\_12130K4  
TEST LAB: BEGA  
DATE: 04/05/2015  
LUMINAIRE: 12 130K4  
LAMP: 14.2W LED




## Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1123
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	62
Total Luminaire Watts	18
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.85 ft (Diameter)
Luminous Height	0.21 ft


## Zonal Lumen Summary

Zone	Lumens
0-10	30.23
10-20	87.31
20-30	133.82
30-40	163.71
40-50	173.53
50-60	162.85
60-70	134.47
70-80	93.31
80-90	46.45
90-100	23.95
100-110	21.48
110-120	17.99
120-130	13.84
130-140	9.69
140-150	6.02
150-160	3.09
160-170	1.13
170-180	0.17



Mounting Height: 10 ft.

Grid Spacing: 5 ft.



Mounting Height: 10 ft.

Grid Spacing: 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/06/20

# BEGA

File: 12130K35\_BEGA\_IES.ies

TEST: BE\_12130K4  
TEST LAB: BEGA  
DATE: 04/05/2015  
LUMINAIRE: 12 130K35  
LAMP: 14.2W LED




## Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1103
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	61
Total Luminaire Watts	18
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.85 ft (Diameter)
Luminous Height	0.21 ft


## Zonal Lumen Summary

Zone	Lumens
0-10	29.69
10-20	85.74
20-30	131.41
30-40	160.76
40-50	170.40
50-60	159.92
60-70	132.05
70-80	91.63
80-90	45.62
90-100	23.52
100-110	21.10
110-120	17.67
120-130	13.59
130-140	9.52
140-150	5.91
150-160	3.04
160-170	1.11
170-180	0.17



Mounting Height: 10 ft.

Grid Spacing: 3 ft.



Mounting Height: 10 ft.

Grid Spacing: 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.



BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/06/20

# BEGA

File: 12130K3\_BEGA\_IES.ies

TEST: BE\_12130K4  
TEST LAB: BEGA  
DATE: 04/05/2015  
LUMINAIRE: 12 130K3  
LAMP: 14.2W LED




## Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1084
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	60
Total Luminaire Watts	18
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.85 ft (Diameter)
Luminous Height	0.21 ft


## Zonal Lumen Summary

Zone	Lumens
0-10	29.18
10-20	84.25
20-30	129.14
30-40	157.98
40-50	167.45
50-60	157.15
60-70	129.77
70-80	90.04
80-90	44.83
90-100	23.11
100-110	20.73
110-120	17.36
120-130	13.36
130-140	9.35
140-150	5.81
150-160	2.98
160-170	1.09
170-180	0.16



Mounting Height: 10 ft.

Grid Spacing: 3 ft.



Mounting Height: 10 ft.

Grid Spacing: 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.



BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/06/20

# BEGA

File:12130K27\_BEGA\_IES.ies

TEST: BE\_12130K4  
TEST LAB: BEGA  
DATE: 04/05/2015  
LUMINAIRE: 12 130K27  
LAMP: 14.2W LED




## Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1076
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	60
Total Luminaire Watts	18
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.85 ft (Diameter)
Luminous Height	0.21 ft


## Zonal Lumen Summary

Zone	Lumens
0-10	28.96
10-20	83.64
20-30	128.20
30-40	156.83
40-50	166.24
50-60	156.01
60-70	128.83
70-80	89.39
80-90	44.50
90-100	22.95
100-110	20.58
110-120	17.24
120-130	13.26
130-140	9.29
140-150	5.77
150-160	2.96
160-170	1.08
170-180	0.16



Mounting Height: 10 ft.

Grid Spacing: 3 ft.



Mounting Height: 10 ft.

Grid Spacing: 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2020

07/06/20