

**Application**

This luminaire is a unique combination of the age-old glassmaker's art with the latest lighting technology. The shallow design is only possible with the integration of compact, reliable and cost-effective LED sources. Available in three housing finishes and an opal glass diffuser, allowing for the perfect coordination with other architectural details.

**Materials**

Three-ply opal glass satin matte finish  
Aluminum housing

**NRTL** listed to North American Standards, suitable for damp locations  
Weight: 5.3lbs

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	14.2W
System wattage	18.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,123 lumens (4000K)
LED service life (L70)	60,000 hours

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number <b>.1</b>
	Stainless steel	Code number <b>.2</b>
	Polished aluminum	Code number <b>.3</b>



**Ceiling and wall luminaire**

	LED	A	B
<b>12130</b> <small>ADA</small>	14.2W	10 <sup>3</sup> / <sub>8</sub>	2 <sup>1</sup> / <sub>2</sub>

