

Application

Designed for low mounting heights for interior and exterior locations, the asymmetrical wide spread light distribution is ideally suited for illuminating corridors and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass with optical texture
 Reflector made of pure anodized aluminum
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 4.4 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	11.7 W
System wattage	16 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	777 lumens (3000K)
Lifetime at Ta = 25° C	50,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED recessed wall · asymmetrical wide spread light distribution

	LED	A	B
22056	11.7 W	9 ⁷ / ₈	4 ⁷ / ₈

Type:
 BEGA Product:
 Project:
 Modified:

Available Accessories

19523 Concrete protection cover
 See individual accessory spec sheet for details.

