

Application

Designed for low mounting heights for interior and exterior locations, the unshielded luminaire has a directing and guiding lighting effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Faceplate constructed of 316 grade machined stainless steel
 White safety glass
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP64

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -20°C
 LED module wattage 10.1 W
 System wattage 11.5 W
 Controllability 0-10V, TRIAC, and ELV dimmable
 Color rendering index $Ra > 80$
 Luminaire lumens 91 lumens (3000K)
 Lifetime at $T_a = 25^{\circ}\text{C}$ 50,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3 (EXPRESS)**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel.
 Custom colors are not available.
 Stainless steel requires regular cleaning and maintenance, much like household appliances to maintain its luster and prevent tarnishing or the appearance of rust like stains.



LED recessed wall · unshielded				
	LED	A	B	C
22 132	ADA 10.1 W	12 3/4	3 1/8	4

Type:
 BEGA Product:
 Project:
 Modified:

Available Accessories

19601 Concrete protection cover
 See individual accessory spec sheet for details.

