

Application

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Faceplate constructed of 316 grade machined stainless steel  
Clear safety glass with optical texture  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 64

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30°C
LED module wattage	3.4 W
System wattage	4.9 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	9 lumens (3000K)
Lifetime at Ta = 25°C	50,000 h (L70)


LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3 (EXPRESS)**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel.  
Custom colors are not available.  
Stainless steel requires regular cleaning and maintenance, much like household appliances to maintain its luster and prevent tarnishing or the appearance of rust like stains.



LED recessed wall · shielded				
	LED	A	B	C
22 135	ADA 3.4 W	7 1/2	3 1/8	4

Type:

BEGA Product:

Project:

Modified:

Available Accessories

**19535** Concrete protection cover  
See individual accessory spec sheet for details.

