

Application

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
White safety glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 3.5 lbs

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 7.7 W
System wattage 11 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 241 lumens (3000K)
Lifetime at Ta = 15° C >500,000 h (L70)
Lifetime at Ta = 30° C 332,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS:

Type:
BEGA Product:
Project:
Modified:

Available Accessories
19522 Concrete protection cover
See individual accessory spec sheet for details.



| LED recessed wall · shielded | | | | | |
|------------------------------|-----|-------|-----|-----|---|
| | | LED | A | B | C |
| 22372 | ADA | 7.7 W | 7 ½ | 7 ½ | 4 |

