BEGA

Photometric Filename: 22433.IES

TEST: BE_22433
TEST LAB: BEGA
DATE: 10/9/2014
LUMINAIRE: 22 433
LAMP: 25.3W



Characteristics

NEMA Type	6 H x 5 V
Maximum Candela	1781.3
Maximum Candela Angle	0 H 37.5 V
Horizontal Beam Angle (50%)	70.0
Vertical Beam Angle (50%)	43.5
Horizontal Field Angle (10%)	115.6
Vertical Field Angle (10%)	95.4
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	794
Beam Efficiency	N.A.
Field Lumens	1659
Field Efficiency	N.A.
Spill Lumens	125
Luminaire Lumens	1784
Total Efficiency	N.A.
Total Luminaire Watts	32

Zonal Lumen Summary

Zone	Lumens
0-10	0.00
10-20	0.00
20-30	0.00
30-40	0.00
40-50	0.00
50-60	0.00
60-70	0.00
70-80	0.00
80-90	0.00
90-100	2.55
100-110	57.54
110-120	206.20
120-130	332.46
130-140	391.30
140-150	349.62
150-160	241.91
160-170	144.75
170-180	50.81





Wall Mount - Isofootcandle grid on ceiling
Distance to ceiling = 5 ft. Grid Spacing = 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.