

Application

Designed for indirect or direct lighting effects for interior and exterior locations. This LED wall luminaire is for illuminating surfaces adjacent to the installation surface, such as ceilings, arches, and canopies.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
White safety glass
Reflector made of pure anodized aluminum
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 11.5lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	50.6 W
System wattage	54 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2982 lumens (3000K)
Lifetime at Ta = 15° C	370,000 h (L70)
Lifetime at Ta = 25° C	280,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED wall luminaire · asymmetric floodlight				
	LED	A	B	C
22434	50.6 W	10 ¼	8 ½	9 ⅝

Type:
BEGA Product:
Project:
Modified:

