


BEGA

Photometric Filename: 22650.IES

TEST: BE_22650
TEST LAB: BEGA
DATE: 3/30/2017
LUMINAIRE: 22 650
LAMP: 3.9W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	327
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	65
Total Luminaire Watts	5
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.38
Spacing Criterion (90-270)	1.38
Spacing Criterion (Diagonal)	1.54
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.56 ft
Luminous Width (90-270)	0.56 ft
Luminous Height	0.11 ft

Zonal Lumen Summary

Zone	Lumens
0-10	6.75
10-20	19.38
20-30	30.48
30-40	39.31
40-50	44.55
50-60	44.78
60-70	38.66
70-80	27.21
80-90	17.49
90-100	15.32
100-110	15.02
110-120	12.29
120-130	8.64
130-140	4.89
140-150	1.95
150-160	0.33
160-170	0.00
170-180	0.00



Wall Mount - Isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 5 ft.



Ceiling Mount - Isofootcandle grid on floor
Mounting Height = 10 ft. Grid Spacing = 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

4/24/2018