

**Application**

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and pathways.

**Materials**

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy

White safety glass

Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Stainless steel screw clamps

Composite installation housing

**NRTL** listed to North American Standards, suitable for wet locations

Protection class IP65

Weight: 1.7 lbs

**Electrical**

Operating voltage 120-277VAC

Minimum start temperature -40°C

LED module wattage 3.8W

System wattage 6.0W

Controllability 0-10V dimmable

Color rendering index Ra > 80

Luminaire lumens 379 lumens (4000K)

LED service life (L70) 50,000 hours

**LED color temperature**

4000K - Product number + **K4**

3500K - Product number + **K35**

3000K - Product number + **K3**

2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors      Black (BLK)      White (WHT)      RAL:  
                            Bronze (BRZ)      Silver (SLV)      CUS:



• A • B •

**Recessed wall luminaire - unshielded**

	LED	A	B
<b>24011</b>	ADA	3.8 W	5 1/8    5 1/2

Type:

BEGA Product:

Project:

Modified:

