

Application

Designed for accent lighting of walls and facades. Four wide beams of light produce a striking pattern on the installation surface in any orientation.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
Silicone optics
Silicone applied robotically to casting, plasma treated for increased adhesion
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 4.0lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	20.0 W
System wattage	24.0 W
Controllability	0-10V, Triac, ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	812 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Wall Luminaire · Four 90° ports				
	LED	A	B	
24 045	ADA	20.0 W	7 1⁄8	2 7⁄8

Type:

BEGA Product:

Project:

Modified:

