

Application

Designed for accent lighting of walls and facades. A variety of beam angles produce a striking pattern on the installation surface in any orientation.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Clear safety glass with optical texture  
Silicone optics  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 4.0lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	17.0W
System wattage	21.0W
Controllability	0-10V, Triac, ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	717 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:

Project:

Modified:



Wall Luminaire · Three 90° ports · One 15° port

	LED	A	B
24 046	ADA 17.0W	7 1/8	2 7/8