

Application

LED recessed wall luminaire with asymmetrical forward throw distribution for superior illumination of ground surfaces from an extremely low mounting height. The optimal mounting height between 1' and 1.5' above finished grade.

Materials

- Luminaire housing constructed of die-cast aluminum marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- Clear safety glass
- Reflector made of pure anodized aluminum
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP65
Weight: 4.4 lbs

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30°C
- LED module wattage12.2 W
- System wattage15.0 W
- ControlabilityTRIAC, ELV and 0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens848 lumens (3000K)
- Lifetime at Ta=15°C67,000 h (L70)
- Lifetime at Ta=35°C55,000 h (L70)

LED color temperature

- 2700K - Product number + **K27**
- 3000K - Product number + **K3**
- 3500K - Product number + **K35**
- 4000K - Product number + **K4**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:
BEGA Product:
Project:
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



LED recessed wall luminaires · asym. forward throw				
	LED	A	B	C
24 060	12.2 W	13	5	5½

