

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
White safety glass
Silicone applied robotically to casting, plasma treated for increased adhesion
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Stainless steel screw clamps
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 2.2lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	5.8 W
System wattage	9.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	644 lumens (4000K)
LED service life (L70)	50,000 hours

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



Recessed wall luminaire · unshielded				
	LED	A	B	C
24 215	ADA 5.8 W	5 7⁄8	5 7⁄8	5 1⁄4

Type:
BEGA Product:
Project:
Modified:

