

Application

Compact ceiling mounted downlights designed for down lighting atriums, canopies, passages and other interior and exterior locations.

Materials

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Class A toughened safety glass  
Pure anodized aluminum reflector surface  
Silicone optic with excellent high temperature and UV stability  
Silicone applied robotically to casting, plasma treated for increased adhesion

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 3.75 lbs

Electrical

Operating voltage 120, 220-240 OR 277 VAC  
Minimum start temperature -30° C  
LED module wattage 24.1 W  
System wattage 28.0 W  
Controllability 0-10V, TRIAC, and ELV dimmable  
Color rendering index Ra > 90  
Luminaire lumens 2958 lumens (4000K)  
LED service life (L70) 60,000 hours

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:  
BEGA Product:  
Project:  
Modified:

Available options  
**FSC** Fusing



Surface mounted downlight · narrow beam				
	LED	β	A	B
24 422	24.1 W	14 °	5 3/4	5 7/8

β= Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com