

Application

Compact ceiling mounted downlights with an asymmetric distribution designed for the even illumination of ground surfaces in corridors and other interior and exterior locations.

Materials

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Class A toughened safety glass
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability
Silicone applied robotically to casting, plasma treated for increased adhesion

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 3.75 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	24.1 W
System wattage	28.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	2485 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:
BEGA Product:
Project:
Modified:

Available options
FSC Fusing



Surface mounted downlight · asymmetric wide beam

	LED	A	B
24 432	24.1 W	5 3/4	5 7/8

