

Application

LED recessed wall luminaire with unshielded light and louvers for use as location luminaires for means of way finding.

Materials

Luminaire housing constructed of die-cast aluminum marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
White safety glass  
Silicone applied robotically to plasma treated casting for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Stainless steel screw clamps  
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP65  
Weight: 1.8 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	2.7 W
System wattage	5.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	44 lumens (3000K)
Lifetime at Ta=15° C	120,000 h (L70)
Lifetime at Ta=40° C	78,000 h (L70)

LED color temperature

2700K - Product number + **K27**  
3000K - Product number + **K3**  
3500K - Product number + **K35**  
4000K - Product number + **K4**


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:  
BEGA Product:  
Project:  
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



LED recessed wall luminaires · unshielded location luminaires

	LED	A	B	C
33018	2.7 W	10 1/8	2 3/4	5

