


BEGA

Photometric Filename: 33233.IES

TEST: BE_33233
TEST LAB: BEGA
DATE: 3/10/2017
LUMINAIRE: 33 233
LAMP: 11.5W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	995
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	71
Total Luminaire Watts	14
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.32
Spacing Criterion (90-270)	1.32
Spacing Criterion (Diagonal)	1.46
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.62 ft
Luminous Width (90-270)	0.62 ft
Luminous Height	0.07 ft

Zonal Lumen Summary

Zone	Lumens
0-10	27.25
10-20	79.10
20-30	122.57
30-40	152.46
40-50	165.03
50-60	158.14
60-70	131.72
70-80	88.90
80-90	42.37
90-100	17.39
100-110	8.20
110-120	2.27
120-130	0.01
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.01



Ceiling Mount - Isofootcandle grid on floor
Mounting Height = 10 ft. Grid Spacing = 10 ft.



Wall Mount - Isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

4/12/2018