

**Application**  
Recessed wall luminaire with unshielded light for use as a location luminaire for way finding.

**Materials**  
Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
White safety glass  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Stainless steel screw clamps  
Composite installation housing

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 2.2lbs


<b>Electrical</b>	
Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	2.8 W
System wattage	5.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	331 lumens (4000K)
LED service life (L70)	50,000 hours

**LED color temperature**  
4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



Type:  
BEGA Product:  
Project:  
Modified:



Recessed wall luminaire · location				
	LED	A	B	C
33 296	ADA 2.8 W	5 7⁄8	5 7⁄8	5 1⁄4