


BEGA

Photometric Filename: 44419.IES

TEST: BE_44419
TEST LAB: BEGA
DATE: 3/6/2017
LUMINAIRE: 44 419
LAMP: 30.4W LED




Characteristics

IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1399
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	39
Total Luminaire Watts	36
Ballast Factor	1.00
Upward Waste Light Ratio	N.A.
Max. Cd.	502.5 (180H, 0V)
Max. Cd. (<90 Vert.)	502.5 (180H, 0V)
Max. Cd. (At 90 Deg. Vert.)	.4 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	52.7 (3.8%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	193.6	N.A.	13.8
FM (30-60)	360.5	N.A.	25.8
FH (60-80)	122.0	N.A.	8.7
FVH (80-90)	6.0	N.A.	0.4
BL (0-30)	195.7	N.A.	14.0
BM (30-60)	375.2	N.A.	26.8
BH (60-80)	136.7	N.A.	9.8
BVH (80-90)	8.9	N.A.	0.6
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	1398.6	N.A.	100.0

BUG Rating B1-U0-G0



Wall mount - isofootcandle diagram on floor
Mounting Height = 5 ft. Grid Spacing = 5 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

8/21/2018