

Application

This unique, slightly convex opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

Three-ply opal glass satin matte finish with screw neck
Luminaire housing constructed of aluminum alloy

NRTL listed to North American Standards, suitable for damp locations
Weight: 1.8lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	17.8 W
System wattage	23.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,934 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:

Mounting options

CP12121 Ceiling Pan
(0-10V dimmable down to 0.1%)



Semi-recessed ceiling and wall luminaire

	LED	A	B	C
50 171 ADA	17.8 W	11 3⁄8	2 3⁄8	1 3⁄8