

Application

A versatile family of luminaires, the asymmetric light distribution version is intended to indirectly illuminate ceilings or archways, while also subtly illuminating the wall surface. These luminaires are an excellent lighting tool for efficient, indirect illumination of interior spaces.

Materials

Die-cast aluminum housing  
Reflector surface made of pure anodized aluminum  
Clear safety glass

**NRTL** listed to North American Standards, suitable for damp locations  
Weight: 6.4 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	33.6 W
System wattage	41.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	2,927 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number <b>.1</b>
	Palladium	Code number <b>.4</b>
	Velvet black	Code number <b>.5</b>



Wall washer · Asymmetric light distribution

	LED	A	B	C
<b>50 201</b>	33.6 W	12 5/8	4 1/8	7 3/8

Type:

BEGA Product:

Project:

Modified:

