

Application

This unique, slightly convex opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

Luminaire housing constructed of aluminum alloy
Three-ply opal glass satin matte finish with screw neck
Silicone gasket

NRTL listed to North American Standards, suitable for damp locations
Weight: 1.8lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	8.5W
System wattage	13.0W
Controllability	DALI-2 controlled
Color rendering index	Ra > 90
Luminaire lumens	596 lumens (6500K)
LED service life (L70)	60,000 hours

LED color temperature

Tunable white color temperature range is adjustable from 2700K to 6500K via the DALI-2 control protocol.



BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Mounting options
CP50289 Ceiling Pan (DALI-2 controlled)



Semi-recessed ceiling and wall luminaire · Tunable white					
		LED	A	B	C
50 202	ADA	8.5 W	8 3⁄8	2 3⁄8	1 1⁄4