

Application

Luminaire with high light output, characterized by its low profile and shallow recessed depth, available with tunable white technology. This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space. This luminaire is equipped with a mounting system for easy, economic, and convenient installation.

Materials

Three-ply opal glass satin matte finish with screw neck  
Luminaire housing constructed of aluminum alloy

**NRTL** listed to North American Standards, suitable for damp locations  
Weight: 5.5lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	28.1 W
System wattage	33.0 W
Controllability	DALI-2 controlled
Color rendering index	Ra > 90
Luminaire lumens	2,109 lumens (6500K)
LED service life (L70)	60,000 hours

LED color temperature

Tunable white color temperature range is adjustable from 2700K to 6500K via the DALI-2 control protocol.

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number <b>.1</b>
	Stainless steel	Code number <b>.2</b>

Type:


BEGA Product:

Project:

Modified:

Mounting options

**CP50291** Ceiling Pan (DALI-2 controlled)



Recessed ceiling and wall luminaire - Tunable white

	LED	A	B
<b>50 291</b> <b>ADA</b>	28.1 W	13 3/8	2 3/8