

Application

Pendant mounted LED cylinder luminaire with a wide light distribution. The partially frosted, crystal glass provides glare control while adding sparkle to any space. The simple clean lines make this ideal for any architectural style.

Materials

Crystal glass diffuser, partially frosted with screw neck
Reflector surface made of pure anodized aluminum
Aluminum housing and canopy
White or black connecting cable

NRTL listed to North American Standards, suitable for damp locations

Weight: 10.1 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30°C
LED module wattage	36.8W
System wattage	41.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3,064 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2
	Polished aluminum	Code number .3

**Pendant luminaire**

	LED	β	A	B	C
50 343	36.8W	34°	4 1/4	21 5/8	118

β = Beam angle

Type:

BEGA Product:

Project:

Modified:

