

Application

Luminaire with high light output, characterized by its low profile and shallow recessed depth. This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space. This luminaire is equipped with a mounting system for easy, economic, and convenient installation.

Materials

Three-ply opal glass satin matte finish with screw neck
Luminaire housing constructed of aluminum alloy
NRTL listed to North American Standards, suitable for damp locations
Weight: 2.1 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	8.4 W
System wattage	12.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	570 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details



Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2

Type:
BEGA Product:
Project:
Modified:

Available options
CP50523 Ceiling Pan
(0-10V dimmable down to 0.1%)



Recessed ceiling and wall luminaire				
	LED	A	B	
50 523	ADA 8.4 W	7 1⁄8	2 3⁄8	