

Application

Hand-blown, three-ply opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

Three-ply opal glass satin matte finish
Luminaire housing constructed of aluminum alloy

NRTL listed to North American Standards, suitable for damp locations
Weight: 10.4lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	43.7 W
System wattage	50.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3,200 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:

Available options

- CP50526-120V** Ceiling Pan - 120V only
(0-10V dimmable down to 0.1%)
- CP50526-277V** Ceiling Pan - 277V only
(0-10V dimmable down to 0.1%)



Semi-recessed ceiling and wall luminaire · Opal glass

	LED	A	B
50 530 ADA	43.7 W	17 1/8	2 3/8