

Application

Compact ceiling and wall luminaire with unshielded light. Elegant luminaire housing without any visible fasteners. A die-cast aluminum housing and thick-walled crystal glass combined with LED technology makes this luminaire a durable and cost-effective solution for interior spaces.

Materials

Luminaire housing constructed of die-cast aluminum alloy
Crystal glass diffuser with white interior finish

NRTL listed to North American Standards, suitable for damp locations
Weight: 6.4 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	15.2 W
System wattage	19.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,461 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2
	Chrome	Code number .3



Ceiling and wall luminaire

	LED	A	B
50 537 ADA	15.2W	10 ¼	3 ⅞

