

Application

This recessed downlight's unique beauty and versatility is enhanced by the choice of four matte interior finishes combined with a white trim finish. These finishes may be chosen to complement a wide array of interior spaces. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Acrylic diffuser
Reflector with matte interior finish
Die-cast and extruded aluminum housing with white finish

NRTL listed to North American Standards, suitable for damp locations
Weight: 1.0lbs

Electrical

Operating voltage	120 or 277VAC
Minimum start temperature	-20°C
LED module wattage	10.0W
System wattage	12.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	757 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.



Available finishes	White	Code number .1
	Matte aluminum	Code number .2
	Matte brass	Code number .4
	Matte copper	Code number .6

Available options**CP50576-120V**

Ceiling pan - 120V only
(0-10V dimmable down to 0.1%)

CP50576-277V

Ceiling pan - 277V only
(0-10V dimmable down to 0.1%)

**STUDIO LINE- Downlight**

	LED	β	A	B
50578	10.0W	65°	5 1/8"	3"

β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2020 Updated 08/14/20