


**Tools Required:**

- Philips head screwdriver medium
- Flat head screwdriver medium

**Overview:**

LED Watts: 23.4W  
System Watts: 28.0W  
Controllability: Triac, ELV, 0-10V dimmable  
Weight: 11.2 lbs.



**Dimensions**

**A:** 13-7/8"  
**B:** 3-5/8"




**Notice to Installer:**

1. See page 2 for specific product safety warnings.
2. Mounts to the ceiling or wall over the standard recessed 4" octagonal junction box.
3. LEDs are high-quality electronic components! Please avoid touching the light output opening of the LED directly during installation.

**Installation:**

1. Remove luminaire glass by twisting counter-clockwise to disengage from luminaire back plate.
2. Make supply wiring and luminaire wiring connections inside the recessed junction box:  
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE  
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE  
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE  
0-10V Dimming (if applicable):  
DIMMING CONTROL WIRE (+) TO POSITIVE DRIVER PURPLE DIM CONTROL WIRE  
DIMMING CONTROL WIRE (-) TO NEGATIVE DRIVER GRAY DIM CONTROL WIRE
3. Mount luminaire to ceiling or wall over the recessed 4" octagonal junction box using hardware by others. See Figure 1 for mounting hole dimensions.
4. Replace luminaire glass by placing over luminaire back plate and rotating clockwise until clips lock in glass in place.

**Figure 1:**



**Accessories**

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

**Maintenance:**

Clean regularly with solvent-free cleaner removing dust and debris.

**Replacement Parts**

See label inside of fixture for LED replacement part number.  
Consult factory for all other replacement components.

**Product Safety Warnings:**

**THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR DAMP LOCATIONS. MIN 90°C SUPPLY CONDUCTORS.**

**CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS HUMIDE.**

**LES FILS D'ALIMENTATION 90°C MIN.**