

Application

A perfectly shaped sphere is one of the most important elements of design. As a fundamental geometric shape, the form is pure and timeless. This captivating wall and ceiling luminaire complements any design aesthetic, making it well suited for a multitude of space types.

Materials

Three-ply opal glass satin matte finish with matte finish
Luminaire housing constructed of aluminum alloy

NRTL listed to North American Standards, suitable for damp locations
Weight: 6.8lbs

Electrical


| | |
|---------------------------|----------------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -20° C |
| LED module wattage | 13.5 W |
| System wattage | 17.0 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 1,626 lumens (4000K) |
| LED service life (L70) | 60,000 hours |

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:



Semi-recessed ceiling and wall luminaire · Unshielded

| | LED | A | B |
|---------------|--------|--------|---|
| 50 636 | 13.5 W | 11 3/4 | 2 |

Available options
CP50636 Ceiling Pan
(0-10V dimmable down to 0.1%)

