

Application

LED pendant with directed and diffuse light distributions, available in three exterior finishes. Light is directed downward by a precise reflector while additional high angle light illuminates the opal glass accent. The dual light distribution results in an efficient luminaire with a high degree of visual comfort.

Materials

Three-ply opal glass
Molded silicone lens
Reflector surface made of pure anodized aluminum
Aluminum housing and canopy
White or black connecting cable

NRTL listed to North American Standards, suitable for damp locations
Weight: 6.4 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	17.0 W
System wattage	21.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,867 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2
	Velvet black	Code number .5



Pendant luminaire					
	LED	β	A	B	C
50 640	17.0 W	50°	7	9	120

β = Beam angle

Type:

BEGA Product:

Project:

Modified:

