Application
Designers often have two wishes when it comes to creating a comfortable interior space: illuminate horizontal surfaces for task lighting, and provide vertical illumination to fill the space. This large-area pendant luminaire's downlight component provides efficient task lighting for floor or table surfaces, while the diffuse cylinder glows to create comfortable ambient lighting.

Materials
White high density polyethylene diffuser
Metal housing and canopy, white finish
Three steel wires
Transparent connecting cable

NRTL listed to North American Standards, suitable for damp locations
Weight: 26.5 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	105.6 W - Diffuse 16.8 W - Downlight
System wattage	149.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	14,566 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

☐ 4000K - Product number + **K4**
☐ 3500K - Product number + **K35**
☐ 3000K - Product number + **K3**
☐ 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
Select the desired material finish by using appropriate code number as suffix.

Available finishes ☐ White Code number **.1**

Type:
BEGA Product:
Project:
Modified:



Large-area pendant luminaire

	LED		β	A	B	C
50 673	105.6 W	Diffuse		7 ½	70	156
	16.8 W	Downlight	49°			

β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2020
Updated 08/12/20