

Ceiling luminaire - shielded
STUDIO LINE

BEGA

Application

This ceiling mounted downlight's unique beauty and versatility is enhanced by the choice of three matte interior finishes combined with a white exterior finish. These finishes may be chosen to complement a wide array of interior spaces. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Die-cast aluminum housing with white painted exterior finish
Matte interior metal finish
Reflector surface made of pure anodized aluminum
Molded silicone lens

NRTL listed to North American Standards, suitable for damp locations
Weight: 2.4 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	11.5 W
System wattage	13.2 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,233 lumens (4000K - Matte aluminum)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White · Matte aluminum	Code number .2
	White · Matte brass	Code number .4
	White · Matte copper	Code number .6

Type:
BEGA Product:
Project:
Modified:



Ceiling luminaire · Shielded				
	LED	β	A	B
50 678	11.5 W	33°	5 ³ / ₈	4 ⁷ / ₈

β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2019 Updated 06/29/20