

Application

This compact luminaire is characterized by high light output and minimal recessed depth. The thick-walled crystal glass brings sparkle and added interest to any ceiling surface, while the inner frosted sections provide glare control.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Reflector made of pure anodized aluminum  
Silicone optic  
Partially frosted crystal glass  
Synthetic recessed ceiling installation housing  
Ceiling mounted driver enclosure constructed of aluminum, a minimum of 7" ceiling clearance is required for installation

NRTL listed to North American Standards, suitable for damp locations  
Weight: 5.3 lbs

Electrical

Operating voltage	120-277 V
Minimum start temperature	-20° C
LED module wattage	17.2 W
System wattage	21.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1,727 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Available finishes	White	Code number <b>.1</b>
	Stainless steel	Code number <b>.2</b>

Type:


BEGA Product:

Project:

Modified:

Available options

**CP50376** Ceiling pan (0-10V dimming only)



Semi-recessed downlight				
	LED	β	A	B
50 695	17.2 W	50°	8	4 3/4

β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2020 Updated 07/27/20