

Application

This pendant mounted luminaire features a wide beam distribution and is available in three finishes. The partially frosted, crystal glass provides glare control while adding sparkle to any space. The simple shape makes these ideal for any architectural style. Coupled with the latest LED technology, this luminaire is an efficient, long service life lighting solution for spaces where architectural interest is a part of the lighting requirement.

Materials

Crystal glass diffuser, partially frosted with screw neck
Reflector surface made of pure anodized aluminum
Metal housing and canopy
Black or white connecting cable

NRTL listed to North American Standards, suitable for damp locations
Weight: 4.4 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	11.5 W
System wattage	13.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,196 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2
	Chrome	Code number .3



Pendant luminaire				
	LED	A	B	C
50 700	11.5 W	5 1/4	7 1/8	84

Type:
BEGA Product:
Project:
Modified:

