

**Application**

A decorative semi-recessed downlight, designed for a diverse range of applications. The decorative glass featured in this luminaire is intended to add interest and depth to interior spaces. Designed with a very small aperture, this luminaire is ideal for both new and retrofit construction.

**Materials**

Three-ply opal glass satin matte finish  
 Reflector made of pure anodized aluminum  
 Die-cast aluminum housing  
 Ceiling mounted driver enclosure constructed of aluminum

**NRTL** listed to North American Standards, suitable for damp locations  
 Weight: 0.8 lbs

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	5.8 W
System wattage	7.7 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	684 lumens (4000K)
LED service life (L70)	60,000 hours

**LED color temperature**

4000K - Product number + **K4**  
 3500K - Product number + **K35**  
 3000K - Product number + **K3**  
 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Available finishes	White	Code number <b>.1</b>
	Polished Stainless steel	Code number <b>.2</b>
	Polished aluminum	Code number <b>.3</b>
	Brass	Code number <b>.4</b>

Type:


BEGA Product:

Project:

Modified:

**Available options**

**19 516** Ceiling Pan (0-10V dimming down to 0.1%)

**ACCENTA - Semi-recessed ceiling luminaire - Unshielded**

	LED	A	B	C
<b>50 717</b>	5.8 W LED	3 1/8	1 7/8	1 1/2

β= Beam angle

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
 © copyright BEGA 2020 Updated 07/24/20