

Application

A very compact ceiling mounted downlight with partially frosted crystal glass. This luminaire is designed for down lighting atriums, canopies, passages and other interior and exterior locations.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Partially frosted crystal glass
 Reflector made of pure anodized aluminum
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 4.4lbs

Electrical

Operating voltage 120-277 VAC
 Minimum start temperature -30°C
 LED module wattage 10.0W
 System wattage 11.5W
 Controllability 0-10V, TRIAC, and ELV dimmable to 1%
 Color rendering index $Ra > 80$
 Luminaire lumens 854 lumens (4000K)
 LED service life 60,000 h (L70)

LED color temperature

- 4000K - Product number + **K4 (EXPRESS)**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3 (EXPRESS)**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:
 BEGA Product:
 Project:
 Modified:

Available options
FSC Fusing

See individual accessory spec sheet for details.



Surface mounted downlight · Partially frosted crystal glass

	LED	β	A	B
66 051	10.0W	57°	$5\frac{7}{8}$	$5\frac{1}{4}$

β = Beam angle

