

Application

A very compact ceiling mounted downlight with partially frosted crystal glass. This luminaire is designed for down lighting atriums, canopies, passages and other interior and exterior locations.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Partially frosted crystal glass
Reflector made of pure anodized aluminum
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 2.6lbs

Electrical

Operating voltage	120-277 VAC
Minimum start temperature	-30° C
LED module wattage	4.8 W
System wattage	6.4 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	591 lumens (4000K)
LED service life	60,000 h (L70)

LED color temperature

4000K - Product number + **K4 (EXPRESS)**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:
BEGA Product:
Project:
Modified:

Available options
FSC Fusing
MGU Marine grade undercoat
See individual accessory spec sheet for details.



Surface mounted downlight · Partially frosted crystal glass				
	LED	β	A	B
66 056	4.8 W	65°	4 ⁷ / ₈	4 ⁵ / ₈

β= Beam angle

