

Application

A bollard with shielded asymmetric light distribution. Designed for effective lighting of landscapes, pathways, and open spaces. The fully shielded design provides visual comfort while illuminating ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Luminaire housing constructed of die-cast and extruded marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Clear safety glass
- Reflector made of pure anodized aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Mounting plate constructed of heavy cast aluminum

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 13.9lbs

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage11.5 W
- System wattage18.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens1743 lumens (4000K)
- LED service life (L70)60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Shielded bollard · Asymmetric				
	LED	A	B	Anchorage
84 239	11.5W	7 ½	39 ⅝	79817

Type:
BEGA Product:
Project:
Modified:

Available options
EMPK Integral emergency battery pack
70895 Direct burial anchorage

