

Application

System bollard head with 360° light distribution. Simply order the bollard head and also the required bollard tube in various heights and options. Both modules can be joined together easily and quickly during installation.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Clear safety glass  
Reflector made of pure anodized aluminum  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Interlocking stainless steel mounting mechanism

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP65  
Weight: 14.3lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	15.6 W
System wattage	21.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,668 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:


Project:

Modified:

Compatible bollard tubes (select one)

<b>99 615</b>	No access door - height 14 ½
<b>99 622</b>	With access door - height 32 ½
<b>99 644</b>	Integral floodlight
<b>99 626</b>	Integral GFCI outlet
<b>99 658</b>	Passive infrared motion sensor
<b>99 635</b>	Emergency lighting battery
<b>84 464</b>	Wood bollard tube

See individual bollard tube specification sheet for details.



System bollard head · shielded with reflector · 360°

	LED	A	B	C
<b>84 244</b>	15.6 W	14	8 ½	7 ½