

Application

Light building element with asymmetric light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Class A toughened safety glass with optical texture
 Extruded aluminum pole shaft
 Pure anodized aluminum reflector
 High temperature silicone gasket
 Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Effective projection area: 9.7 sq. ft.
 Weight: 76.7 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	35.2 W
System wattage	43.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	5042 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Building element · asymmetric · twin

	LED	A	B	C	Anchorage
84 276	35.2 W	9 1/4	18	137 3/4	79 802

Type:
 BEGA Product:
 Project:
 Modified:

Available options

- 71 140** Direct burial anchorage
- FSC** Fusing

