

Application

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas, roadways and walkways. Provided with slip fitter to fit 3" O.D. poles.

Materials

Luminaire housing and pole fitter constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Clear acrylic diffuser with optical texture  
Reflector made of pure anodized aluminum  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP65  
Effective projection area: 1.61 sq. ft.  
Weight: 61.7lbs

Electrical

Operating voltage	120-277V
Minimum start temperature	-30° C
LED module wattage	100.8W
System wattage	114W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	8,978 lumens (3000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Pole-top luminaire · asymmetric			
	LED	A	B
84 306	100.8W	29 1/2	32 3/8

\* Recommended for use with 20' to 25' poles

Type:  
BEGA Product:  
Project:  
Modified:

