

Application

The shielded design of this bollard provides visual comfort while illuminating ground surfaces. This wide asymmetric distribution is ideal for illuminating pathways with optimal spacing between luminaires. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass
- 100% recycled B231 aluminum alloy
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Anchor bolts provided with (2) hex nuts and (2) flat washers
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 27.1 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	11.5 W
System wattage	18.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1514 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Bronze (BRZ)	Black (BLK)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

70896	Direct burial anchorage
CUS	Custom finish
DALI-2	Digital addressable lighting interface
EMPK	Integral emergency battery pack
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish



Bollard · Asymmetric wide beam				
	LED	A	B	C
B84462	11.5 W	8 ⁵ / ₈	38 ⁷ / ₈	8 ⁵ / ₈