

Application

Light building element with symmetric light distribution. Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

- Clear safety glass
- A380 aluminum alloy
- High-strength A572 stainless steel alloy
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 59.5lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- Maximum ambient temperature50° C
- LED module wattage19.5W
- System wattage24.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1500 lm

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

- B71207Direct burial anchorage
- CUSCustom finish
- DALI-2Digital addressable lighting interface
- FSCFusing
- MGUMarine grade undercoat
- RALRAL finish

Included (available for pre-shipment)

- B79827Anchorage kit



Building element · Symmetric

	LED	A	B	C
B84754	19.5W	6 <sup>1</sup> / <sub>4</sub>	99 <sup>7</sup> / <sub>8</sub>	137 <sup>3</sup> / <sub>4</sub>

