

Light Building Element - symmetric distribution, two adjustable floodlights

BEGA

Application

Light Building Elements are luminous design features for public areas. These luminaires are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances, and atria. Provided with two integral floodlight to accentuate facades, trees, and other design elements in public spaces. The floodlights are adjustable from 0° to 30° and can be rotated 360°, flat beam and wide beam options available.

Materials

Luminaire housing and post constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
UV stabilized acrylic diffuser
Clear safety glass
Reflector made of pure anodized aluminum
Silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 87.5 lbs.

EPA (Effective projection area): 11.84 sq. ft.

Electrical

Operating voltage	120-277V AC (surge protection)
Minimum start temperature	-40° C
Maximum ambient temperature	40° C
LED module wattage	31.0 W (luminaire) 2 x 5.7 W (floodlights)
System wattage	50.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3,370 lumens (4000K, luminaire) 581 lumens (4000K, floodlight)
LED service life (L70)	60,000 hours

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Light Building Element - symmetric distribution, two adjustable floodlights

	LED	β	A	B	C	D
88 865	31.0 W 2 x 5.7 W	16°	6 ⁵ / ₈	23 ⁵ / ₈	177	31 ¹ / ₂

Type:

BEGA Product:

Project:

Modified:

Available Accessories

10 043 Wide beam spread lens (floodlight)
10 014 Flat beam spread lens (floodlight)



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2018 Updated 01/15/19