

Application

Bollards with wide spread light distribution are perfect for the illumination of walkways and paths. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Luminaire housing and base constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass with optical texture
 Reflector made of pure anodized aluminum
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 18.7 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	17.9W
System wattage	22.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,907 lumens (3000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.


Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:

BEGA Product:

Project:

Modified:



Bollard - wide spread light distribution

	LED	A	B	C	Anchorage
99560	17.9W	9 ⁷ / ₈	43 ³ / ₈	5 1/2	79817