



Ceiling and wall luminaires

A series of low profile ceiling and wall luminaires with hand-blown, three-ply opal or white crystal glass. This family of luminaires can be utilized individually or in groups for glare-free illumination in interior or exterior spaces.


Aluminum housing · Crystal glass inside white or three-ply opal glass

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 64



Opal Glass		LED	A	B
33 680	ADA	14.2 W	10%	2%
33 681	ADA	19.6 W	12	2%



Crystal Glass · inside white		LED	A	B
33 682	ADA	14.2 W	10%	2%
33 683	ADA	19.6 W	12	2%