



Wall luminaires
Unshielded

A series of unshielded wall luminaires with light output in all directions. The linear shape of these luminaires makes them particularly suitable for installation on columns and walls. These luminaires can be installed vertically or horizontally.

BEGA 19 537 small opening wiring box (included) required for proper installation.


Die-cast and extruded aluminum · Three-ply opal glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Wall luminaires						
	LED	A	B	C	D	Required wiring box
24 590	15.6 W	3 1/8"	19 3/4"	4 1/2"	1 5/8"	19 537
24 591	19.8 W	3 1/8"	23 3/4"	4 1/2"	1 5/8"	19 537
24 592	23.6 W	3 1/8"	27 3/4"	4 1/2"	1 5/8"	19 537

