

Wall luminaires

Wall mounted luminaires made of die-cast aluminum and heavy pressed crystal glass. The exceptional material thickness and strength of crystal glass provides this luminaire group with robustness and defines their character. Arranged individually or in groups, they are great design elements for a host of lighting applications.


Die-cast aluminum · Heavy pressed crystal glass inside white

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Wall luminaires · **Shielded on two sides**

	LED	A	B	C
24 071	ADA 11.5 W	9 ½	9 ½	3 ¼



Wall luminaires · **Shielded on one side**

	LED	A	B	C
24 070	ADA 11.5 W	9 ½	9 ½	3 ¼